

# imageRUNNER ADVANCE

6055/i  
6065/i  
6075/i

The next level in  
office productivity.

**you can**

Move your business forward with our most advanced series of multifunctional black and white office devices. Boosting office productivity and transforming document workflows, they offer advanced security capabilities and outstanding environmental credentials.

<b>55 - 75</b> PPM PPM MONO
PERSONAL USER INTERFACE
UP TO 7,700 SHEET PAPER CAPACITY
EXCEPTIONAL SCANNING CAPABILITY
ADVANCED FINISHING CAPABILITIES
MODULAR DESIGN



## Productivity

- Highly intuitive 8.4" colour touch-screen user interface
- Create "one-touch" buttons to execute common tasks
- High speed duplex scanning up to 200 ipm
- Seamless scanning into business applications
- Integrated software options provide powerful end-to-end workflow solutions

## Environmental

- Excellent energy efficiency: as little as 1.5 watts power consumption in sleep mode
- Energy Star certified
- Incorporates recycled materials and Bio plastics

## Security

- Advanced security features spanning document confidentiality, integrity and availability
  - Seamless integration with Canon uniFLOW OM solution
  - Compliance with Common Criteria at EAL3 level\*
- \* Requires optional HDD Data Encryption & Mirroring Kit

## Finishing & Quality

- Advanced finishing (booklet & staple finishing, C & Z folding, inserting, hole punching)
- Superb 1200 dpi print quality
- Optional Genuine Adobe PostScript & Fiery based RIP

 **imageRUNNER**  
ADVANCE

**Canon**

# Specifications: imageRUNNER ADVANCE 6055/i 6065/i 6075/i

<b>BASIC SPECIFICATIONS</b>	<p>Type Console</p> <p>Maximum Original Size A3</p> <p>Copy Sizes Cassette 1, 2: A4 Cassette 3, 4: A3 to A5R, Free size (139.7 x 182mm to 297 x 487.7mm) Stack Bypass: A3 to A5R, Free size (100 x 148mm to 297 x 487.7mm)</p> <p>Resolution Reading: 600dpi x 600dpi, Copying: 1200dpi x 1200dpi Printing: 1200dpi x 1200dpi, 256 Gradations</p> <p>Copy/Print Speed A4: 55 ppm (iR-ADV 6055/i), 65 ppm (iR-ADV 6065/i), 75 ppm (iR-ADV 6075/i), A3: 32 ppm (iR-ADV 6055/i), 32 ppm (iR-ADV 6065/i), 37 ppm (iR-ADV 6075/i)</p> <p>Enlargement/ Reduction Zoom: 25% - 400%</p> <p>First copy time Fixed: Zoom Ratio 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.3 seconds (iR-ADV 6055/i, iR-ADV 6065/i), 3.1 seconds (iR-ADV 6075/i)</p> <p>Warm-Up Time 38 seconds or less</p> <p>Multiple Copies/Prints 1 to 9999 sheets</p> <p>Duplexing Standard Automatic</p> <p>Paper weight Cassettes: 52 to 220g/m<sup>2</sup>, Stack Bypass: 52 to 256g/m<sup>2</sup> Duplex: 52 to 220g/m<sup>2</sup></p> <p>Paper Capacity Standard: 1,500 sheets x 2 Cassettes (3,000 sheets), 550 sheets x 2 Cassettes (1,100 sheets), Stack Bypass: 100 sheets, Optional: Side Paper Deck: 3,500 sheets, Max paper capacity: 7,700 sheets</p> <p>Processor speed 1.2GHz</p> <p>Memory 1.5GB (optional 512MB available)</p> <p>Hard Disk Drive Standard 80GB, Expandable up to 250GB</p> <p>Display 8.4" TFT SVGA Colour Touchscreen, Optional 10.4" TFT SVGA Colour Touchscreen</p> <p>Interface Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN (IEEE802.11b/g, Optional), USB2.0</p> <p>Network Protocols TCP/IP* (LPD/ Port 9100/ WSD/ IPP/ IPPS/ SMB/ FTP), IPX/SPX (NDS, Bindery), AppleTalk *IPv4/IPv6 support</p> <p>Power Supply 220-240V, 10A 50/60Hz</p> <p>Power Consumption 2.2 kW Max.</p> <p>Dimensions (W x D x H) 645mm x 770mm x 1220mm</p> <p>Installation space (W x D) 942mm x 1289mm</p> <p>Weight Approx. 235kg</p>
<b>PRINT SPECIFICATIONS</b>	<p>Page Description Language(s) UFR II (Standard on all models), PCL5e/6: (Standard for i models, Optional for non i-models with Canon PCL Printer Kit-AJ1), Adobe PostScript 3 (Optional on all models with Canon PS Printer Kit-AJ1)</p> <p>Resolution 1200dpi x 1200dpi, 600dpi x 600dpi</p> <p>Fonts PCL fonts: 93 Roman, 10 Bitmap, 2 OCR, PS fonts: 136 Roman</p> <p>Supported Operating Systems UFR II: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, Mac OS X (10.4.9 or later) PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008 / Windows 7/ Server 2008 R2 PS: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, Mac OS X (10.4.9 or later) Mac-PPD: Mac OS 9.1 or later, Mac OS X (10.2.8 or later)</p>
<b>FIERY BASED PRINTING</b>	<p>Name imagePASS-U1 (Optional)</p> <p>Page Description Language(s) Adobe PostScript 3, PCL6 / PCL5e</p> <p>Resolution 1200dpi x 1200dpi, 600dpi x 600dpi</p> <p>Memory 2GB</p> <p>Hard Disk 80GB</p> <p>CPU Intel Core Duo T2500, 2.0GHz</p> <p>Fonts PS: 136 Adobe PS Fonts, PCL: 113 PCL Fonts</p> <p>Supported Operating Systems Windows 2000 (Printer driver only)/ XP (SP3)/Server 2003 (SP2)/ Server 2008 (SP2)/ Vista (SP2)/ Vista SP1 / Windows 7 (Printer driver only), Mac OS (10.4 or later)</p> <p>Interface Ethernet (1000Base-T/100Base-TX/10Base-T), USB, D-sub 15-pin connector</p> <p>Network Protocol TCP/IP (LPD/ Port 9100/ IPP/ SMB/ FTP), ATP/ DDP (AppleTalk)</p>
<b>SCAN SPECIFICATIONS</b>	<p>Optional/Standard Scan Speed Requires optional Duplex Colour Image Reader Unit-C1 Scan (Single side): A4 120 ipm 300dpi (BW), 85 ipm 300dpi (Colour), Scan (Double side): A4 200 ipm 300dpi (BW), 100 ipm 300dpi (Colour)</p> <p>Scan Resolution 100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi (600dpi colour scanning requires optional Memory Type B - 512MB)</p> <p>Pull Scan Via Network TWAIN Driver (75 to 600dpi Black &amp; White and Colour) Pull Scan Supported OS: Windows 2000/ Windows XP/ Windows Server 2003/ Windows Vista/ Windows Server 2008/ Windows 7 (32 bit, 64 bit in compatibility mode)</p>
<b>SEND SPECIFICATIONS</b>	<p>Optional/Standard Destinations Requires optional Duplex Colour Image Reader Unit-C1 E-Mail/ Internet FAX (SMTP), PC (SMB, FTP), WebDAV</p> <p>Address book LDAP, Local (Max 1800)</p> <p>File Format TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web</p> <p>Universal Send Feature Sets: Universal Send Advanced Feature Set-E1 (option): Outline PDF (Trace &amp; Smooth), Searchable PDF/XPS, Reader Extensions PDF Universal Send Security Feature Set-D1 (option): Encrypted PDF, Device Signature PDF/XPS, Universal Send Digital User Signature Kit-C1 (option): User Signature PDF/XPS</p>

<b>DOCUMENT FEEDER</b>	<p>Colour Image Reader Name Duplex Color Image Reader Unit-C1 (Optional)</p> <p>Paper size A3, A4, A4R, A5, A5R</p> <p>Paper weight Single sided original: 38 to 220 g/m<sup>2</sup>, Double sided original: 64 to 220 g/m<sup>2</sup></p> <p>Max. Number of originals 300 sheets (80 g/m<sup>2</sup>)</p> <p>Scanning speed (max.) Copy (Single side): A4 120 ipm 600dpi (B&amp;W) Scan (Single side): A4 120 ipm 300dpi (B&amp;W), 85 ipm 300dpi (Colour) Copy (Double side): A4 120 ipm 600dpi (B&amp;W) Scan (Double side): A4 200 ipm 300dpi (B&amp;W), 100 ipm 300dpi (Colour)</p> <p>Dimensions (WxDxH) 635mm x 605mm x 253mm</p> <p>Weight Approx. 39.4kg</p>
<b>PAPER DECK UNIT-A1</b>	<p>Paper Size A4</p> <p>Paper Weight 52 to 220 g/m<sup>2</sup></p> <p>Paper Capacity 3,500 sheets (80 g/m<sup>2</sup>)</p> <p>Dimensions (W x D x H) 323mm x 583mm x 570mm</p> <p>Weight Approx. 37kg</p>
<b>PAPER DECK UNIT-D1</b>	<p>Paper Size A3, A4, A4R</p> <p>Paper Weight 52 to 220 g/m<sup>2</sup></p> <p>Paper Capacity 3,500 sheets (80 g/m<sup>2</sup>)</p> <p>Dimensions (W x D x H) 601mm x 621mm x 570mm</p> <p>Weight Approx. 57 kg</p>
<b>STAPLE FINISHER-E1 BOOKLET FINISHER-E1</b>	<p>Number of Trays 3</p> <p>Tray Capacity Tray A: A4/A5R 250 sheets, A3/A4R 125 sheets, Tray B: A4/ASR 1,300 sheets, A3/A4R 650 sheets, Tray C: A4 2,450 sheets, A5R 1,700 sheets, A3/A4R 650 sheets</p> <p>Paper Weight 64 to 105 g/m<sup>2</sup></p> <p>Staple Position Corner, Double, Booklet Stitch (Booklet Finisher only)</p> <p>Staple Capacity A4: 50 sheets, A3/A4R : 30 sheets</p> <p>Booklet Stitch Paper Size A3, A4R (Booklet Finisher-E1 only)</p> <p>Booklet Stitch Staple Capacity 16 sheets (64 pages, 64-81g/m<sup>2</sup>) (Booklet Finisher-E1 only)</p> <p>Dimensions (W x D x H) Staple Finisher-E1: 748mm x 656mm x 1121mm Booklet Finisher-E1: 748mm x 656mm x 1121mm</p> <p>Weight Staple Finisher-E1: Approx. 48kg Booklet Finisher-E1: Approx. 70.5kg</p>
<b>PUNCHER UNIT/S</b>	<p>(All Puncher Units require either the Booklet Staple Finisher E1 or Staple Finisher E1)</p> <p>External 2 Hole Puncher-A1: 2 holes, External 2/4 Hole Puncher-A1: 2 holes, 4 holes (French)</p>
<b>DOCUMENT INSERTION/ FOLDING UNIT-H1</b>	<p>Requires either Booklet Finisher-E1 or Staple Finisher-E1</p> <p>Number of insertion trays 1 Tray</p> <p>Paper Size / Paper Weight A3, A4, A4R / 60 to 256 g/m<sup>2</sup></p> <p>Insertion Capacity 100 sheets (80 g/m<sup>2</sup>)</p> <p>C-Fold Paper Size/ Weight A4R/ 60 to 105 g/m<sup>2</sup></p> <p>Z-Fold Paper Size/ Weight A3, A4R/ 60 to 105 g/m<sup>2</sup></p> <p>Output Capacity 40 sheets</p> <p>Dimensions (W x D x H) 662mm x 679mm x 1242mm</p> <p>Weight Approx. 76kg</p>
<b>DOCUMENT INSERTION UNIT-L1</b>	<p>Requires either Booklet Finisher-E1 or Staple Finisher-E1</p> <p>Number of insertion trays 1 Tray</p> <p>Insertion Paper Size A3, A4, A4R</p> <p>Paper Weight 60 to 256 g/m<sup>2</sup></p> <p>Insertion Capacity 100 sheets (80 g/m<sup>2</sup>)</p> <p>Dimensions (W x D x H) 662mm x 679mm x 1242mm</p> <p>Weight Approx. 40kg</p>
<b>ADDITIONAL OPTIONS</b>	<p>Printer Cover-B1, Stamp Ink Cartridge-C1, ADF Access Handle-A1 Direct Print Kit (for PDF/XPS)-H1, Barcode Printing Kit-D1, Data Erase Kit-C1, HDD Data Encryption &amp; Mirroring Kit-C2, Encrypted Printing Software-D1, Secure Watermark-B1, Web Access Software-H1, Access Management System Kit-B1, Expansion Bus-F1, Wireless LAN Board-B1, IPsec Board-B2, 2.5inch/80GB HDD-C1, 2.5inch/250GB HDD-D1, Removable HDD Kit-AD1, Document Scan Lock Kit-A1, SeeQuence compose (For IMAGEPASS-U1), SeeQuence impose (For IMAGEPASS-U1), SeeQuence Suite (For IMAGEPASS-U1), REMOVABLE HDD KIT-B4 (For IMAGEPASS-U1), Super G3 FAX Board-AF1, Super G3 2nd Line Fax Board-AF1, Remote Fax Kit-A1, Tab Feeding Attachment Kit-B1, Staple-J1, Staple Cartridge-D3, Shift Tray-E1, Copy Tray-Q1, Upright Control Panel-A1, Card Reader-C1, Copy Card Reader Attachment-A2, Utility Tray-A1, Control Panel Sheet-B1, Remote Operator's Software Kit-B1, Voice Guidance Kit-F1, Multimedia Reader/Writer-A1, Serial Interface Kit-K1</p>
<p>Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ® and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.</p> <p>Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.</p>	



Canon Inc.  
www.canon.com

Canon Europa N.V.  
www.canon-europe.com

English-UK Edition 0145W411  
© Canon Europa N.V., 2010 (0510)

Canon (UK) Ltd  
Woodhatch, Reigate  
Surrey RH2 8BF  
Tel: 01737 220000  
Fax: 01737 220022  
www.canon.co.uk

Canon Ireland  
Arena Road, Sandyford  
Industrial Estate  
Dublin 18, Ireland  
Tel: 01 2052400  
Fax: 01 2958141  
www.canon.ie